## **ELFCLEAN S 140**





**Degreasing Solvent.** 

## **APPLICATIONS**

• ELFCLEAN S 140 is a premium grade aliphatic petroleum solvent designed to be used as a general purpose industrial degreasing agent. It can be classified as a "low odor" solvent and is very effective in penetrating through baked-on varnish-like deposits, loosening paint films, removing rust preventative coatings, and removing oily residues from parts and machinery.

## **ADVANTAGES**

- Low odor.
- Non-corrosive.
- Non-staining.
- · Easy cleaning.
- Fast drying.

TYPICAL CHARACTERISTICS	METHODS	ELFCLEAN S 140
Appearance	Visual	Clear, Water White Liquid
Saybolt Color		+28 min.
Odor		Mild Petroleum Type
Viscosity at 40°C, cSt	ASTM D 445	< 3.0
Viscosity at 100°F, cSt	ASTM D 445	1.25
Flash Point, TCC, °F	ASTM D 92	142
Density @ 60°F, lbs./gal.	ASTM D 1298	6.54
Specific Gravity @ 60°F/60°F	ASTM D 1298	0.785
Aromatics, % Vol.		< 1.0
Water Content, ppm		< 500
Distillation, IBP, °F		355 - 375
Distallaion DP, °F		400 - 415
Aniline Point, °F		160

CAUTION: This product is classified as combustible. Exercise customary fire safety precautions when using this product. Refer to MSDS for more detailed hazard information.