SAFETY DATA SHEET



1. Identification

Product identifier TUFF CUT HDF

Other means of identification None.

Recommended use Floor Cleaner **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Manufacturer Name QualiChem, Inc.

Address PO Box 926
Salem, VA USA

Telephone +1-540-375-6700

Email customerservice@qualichem.com

Website www.qualichem.com

Emergency Phone Number For Chemical Emergency ONLY (spill, leak, fire, exposure, or accident), 24

hour emergency telephone, call Chemtel at +1-800-255-3924 (US,

Canada); +1-813-248-0585 elsewhere.

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1

Serious eye damage/eye irritation Category 1

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage. Causes serious eye damage.

Precautionary statement

Prevention Do not breathe mist or vapor. Wash thoroughly after handling. Wear eye protection/face

protection. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison

center/doctor. Wash contaminated clothing before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
4-Nonylphenol, branched, ethoxylated		127087-87-0	1 - 5
Ethylene glycol monobutyl ether		111-76-2	1 - 5

Material name: TUFF CUT HDF SDS US

Chemical name	Common name and synonyms	CAS number	%
Potassium hydroxide		1310-58-3	1 - 5
Other components below reportab	le levels		80 - 100

4. First-aid measures

Inhalation If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or Skin contact

poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if **Eve contact**

present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

Ingestion

symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment

During fire, gases hazardous to health may be formed.

and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage

Precautions for safe handling

Provide adequate ventilation. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

5 ppm

2 mg/m3

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре `	Value	
Ethylene glycol monobutyl ether (CAS 111-76-2)	PEL	240 mg/m3	
		50 ppm	
US. ACGIH Threshold Limit Value	s		
Components	Туре	Value	
Ethylene glycol monobutyl ether (CAS 111-76-2)	TWA	20 ppm	
Potassium hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m3	
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Туре	Value	
Ethylene glycol monobutyl	TWA	24 mg/m3	

Biological limit values

1310-58-3)

ether (CAS 111-76-2)

Potassium hydroxide (CAS

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethylene glycol monobutyl ether (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA),	Creatinine in urine	*
		with hydrolysis		

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

Ethylene glycol monobutyl ether (CAS 111-76-2)

Can be absorbed through the skin.

TWA

US - Minnesota Haz Subs: Skin designation applies

Ethylene glycol monobutyl ether (CAS 111-76-2) Skin designation applies.

US - Tennessee OELs: Skin designation

Ethylene glycol monobutyl ether (CAS 111-76-2)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Ethylene glycol monobutyl ether (CAS 111-76-2)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Ethylene glycol monobutyl ether (CAS 111-76-2)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eve/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear appropriate chemical resistant clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

Material name: TUFF CUT HDF

SDS US

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Clear Liquid.
Color Pale Yellow
Odor Mild Floral
Odor threshold Not available.

pH > 12.5

Melting point/freezing point $< 104 \,^{\circ}\text{F} \ (< 40 \,^{\circ}\text{C})$ Initial boiling point and boiling $> 212 \,^{\circ}\text{F} \ (> 100 \,^{\circ}\text{C})$

range

Flash point NONE

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure < 1.0 mm Hg estimated

Vapor density Not available. Relative density Not available.

Solubility(ies)

Solubility (water) COMPLETE

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 1.04 g/cm3 8.70 lb/gal

Percent volatile > 70 % estimated

Specific gravity 1.04

VOC (Weight %) 4.8 lb/gal ASTM 2369-04

10. Stability and reactivity

Reactivity Reacts violently with strong acids. This product may react with oxidizing agents.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

Conditions to avoid

reactions

No dangerous reaction known under conditions of normal use.

Do not mix with other chemicals. Contact with incompatible materials.

Incompatible materials Acids. Oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Material name: TUFF CUT HDF SDS US

Skin contact Causes severe skin burns.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Causes serious eye damage. Eye contact Causes digestive tract burns. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result.

Information on toxicological effects

Not available. Acute toxicity

Causes severe skin burns and eye damage. Skin corrosion/irritation

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylene glycol monobutyl ether (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

12. Ecological information

Ecotoxicity Harmful to aquatic life.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

0.83 Ethylene glycol monobutyl ether

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Material name: TUFF CUT HDF SDS US Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN3266

UN proper shipping name Corrosive liquid, basic, inorganic, n.o.s. (Potassium hydroxide)

Transport hazard class(es)

8 **Class** Subsidiary risk 8 Label(s) Packing group Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

B2, IB2, T11, TP2, TP27 Special provisions

Packaging exceptions 154 Packaging non bulk 202 242 Packaging bulk

IATA

UN3266 **UN number**

UN proper shipping name Corrosive liquid, basic, inorganic, n.o.s. (Potassium hydroxide)

Transport hazard class(es)

Class 8 Subsidiary risk Packing group Ш **Environmental hazards** No. **ERG Code** 8L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed.

Cargo aircraft only

Allowed.

IMDG

UN number UN3266

UN proper shipping name Transport hazard class(es) CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Potassium hydroxide)

Class 8 Subsidiary risk Ш Packing group **Environmental hazards**

> Marine pollutant No. F-A. S-B

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

TDG

UN3266

8

Marine pollutant only when containing 10% or more substances identified as marine pollutants or severe marine pollutant when containing 1% or more substances identified as severe marine pollutants

Read safety instructions, SDS and emergency procedures before handling.

Not established.

16

Potassium hydroxide

Transport in bulk according to Annex II of MARPOL 73/78 and

Not regulated as dangerous goods.

the IBC Code

Material name: TUFF CUT HDF 530 Version #: 01 Issue date: 05-21-2015



IATA; IMDG; TDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Chemical Action Plans, Chemicals of Concern

4-Nonylphenol, branched, ethoxylated (CAS 127087-87-0)

Nonylphenol (NP) and Nonylphenol Ethoxylates (NPEs) Action

Plan

CERCLA Hazardous Substance List (40 CFR 302.4)

Ethylene glycol monobutyl ether (CAS 111-76-2)

Listed. Listed.

Potassium hydroxide (CAS 1310-58-3)

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Ethylene glycol monobutyl ether	111-76-2	1 - 5	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

Material name: TUFF CUT HDF SDS US

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

Ethylene glycol monobutyl ether (CAS 111-76-2)

US. Massachusetts RTK - Substance List

Ethylene glycol monobutyl ether (CAS 111-76-2)

Potassium hydroxide (CAS 1310-58-3)

US. New Jersey Worker and Community Right-to-Know Act

Ethylene glycol monobutyl ether (CAS 111-76-2)

Potassium hydroxide (CAS 1310-58-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethylene glycol monobutyl ether (CAS 111-76-2)

Potassium hydroxide (CAS 1310-58-3)

US. Rhode Island RTK

Ethylene glycol monobutyl ether (CAS 111-76-2)

Potassium hydroxide (CAS 1310-58-3)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

05-21-2015 Issue date

Version # 01

The manufacturer cannot anticipate all conditions under which this information and its product, or Disclaimer

> the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

SDS US