SAFETY DATA SHEET



	1. Identification
Product identifier	XTREME CUT 220C
Other means of identification	None.
Recommended use	Cutting and Grinding Fluid
Recommended restrictions	None known.
Manufacturer/Importer/Supplier	/Distributor information
Manufacturer	
Manufacturer Name	QualiChem, Inc.
Address	PO Box 926
	Salem, VA_USA
Telephone	+1-540-375-6700
Email	customerservice@qualichem.com
Website	www.qualichem.com
Emergency Phone Number	For Chemical Emergency ONLY (spill, leak, fire, exposure, or accident), 24 hour emergency telephone, call Chemtel at +1-800-255-3924 (US, Canada); +1-813-248-0585 elsewhere.
	2. Hazard(s) identification
Physical hazards	Not classified.
Health hazards	Not classified.
Label elements	
Hazard symbol	None.
Signal word	None.
Hazard statement	Not available.
Precautionary statement	
Prevention	Not available.
Response	Wash hands after handling.
Storage	Store away from incompatible materials.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	21.5% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment.
	3. Composition/information on ingredients

Mixtures			
Chemical name	Common name and synonyms	CAS number	%
Distillates, (petroleum), hydrotreated heavy naphthenic		64742-52-5	10 - 20
2-(2-Aminoethoxy)ethanol		929-06-6	1 - 5
Amine neutralized carboxylic acid		Not Available	1 - 5
Amine neutralized carboxylic acid		Not Available	1 - 5
3-lodo-2-propynyl butylcarbamate		55406-53-6	0.1 - 1
o-Phenylphenol		90-43-7	0.1 - 1
Propylene glycol		57-55-6	0.1 - 1
Other components below reportable	levels		60 - 80

air. Call a physician if symptoms develop or persist. soap and water. Get medical attention if irritation develops and persists. er. Get medical attention if irritation develops and persists. Get medical attention if symptoms occur. with eyes may cause temporary irritation. hatically. edical personnel are aware of the material(s) involved, and take precautions to elves. 5. Fire-fighting measures m. Dry chemical powder. Carbon dioxide (CO2). ter jet as an extinguisher, as this will spread the fire. ses hazardous to health may be formed. breathing apparatus and full protective clothing must be worn in case of fire. rs from fire area if you can do so without risk. irrefighting procedures and consider the hazards of other involved materials. e or explosion hazards noted. Accidental release measures sary personnel away. Keep people away from and upwind of spill/leak. Wear steetive equipment and clothing during clean-up. Ensure adequate ventilation. Local
er. Get medical attention if irritation develops and persists. Get medical attention if symptoms occur. with eyes may cause temporary irritation. hatically. edical personnel are aware of the material(s) involved, and take precautions to elves. 5. Fire-fighting measures Im. Dry chemical powder. Carbon dioxide (CO2). ter jet as an extinguisher, as this will spread the fire. ses hazardous to health may be formed. breathing apparatus and full protective clothing must be worn in case of fire. rs from fire area if you can do so without risk. irrefighting procedures and consider the hazards of other involved materials. e or explosion hazards noted. Accidental release measures sary personnel away. Keep people away from and upwind of spill/leak. Wear
Get medical attention if symptoms occur. with eyes may cause temporary irritation. hatically. edical personnel are aware of the material(s) involved, and take precautions to elves. 5. Fire-fighting measures Im. Dry chemical powder. Carbon dioxide (CO2). ter jet as an extinguisher, as this will spread the fire. ses hazardous to health may be formed. breathing apparatus and full protective clothing must be worn in case of fire. Irs from fire area if you can do so without risk. irefighting procedures and consider the hazards of other involved materials. e or explosion hazards noted. Accidental release measures sary personnel away. Keep people away from and upwind of spill/leak. Wear
with eyes may cause temporary irritation. hatically. edical personnel are aware of the material(s) involved, and take precautions to elves. 5. Fire-fighting measures Im. Dry chemical powder. Carbon dioxide (CO2). ter jet as an extinguisher, as this will spread the fire. ses hazardous to health may be formed. breathing apparatus and full protective clothing must be worn in case of fire. rs from fire area if you can do so without risk. irrefighting procedures and consider the hazards of other involved materials. e or explosion hazards noted. Accidental release measures sary personnel away. Keep people away from and upwind of spill/leak. Wear
natically. edical personnel are aware of the material(s) involved, and take precautions to elves. 5. Fire-fighting measures Im. Dry chemical powder. Carbon dioxide (CO2). ter jet as an extinguisher, as this will spread the fire. ses hazardous to health may be formed. breathing apparatus and full protective clothing must be worn in case of fire. Irs from fire area if you can do so without risk. irrefighting procedures and consider the hazards of other involved materials. e or explosion hazards noted. Accidental release measures sary personnel away. Keep people away from and upwind of spill/leak. Wear
edical personnel are aware of the material(s) involved, and take precautions to elves. 5. Fire-fighting measures Im. Dry chemical powder. Carbon dioxide (CO2). ter jet as an extinguisher, as this will spread the fire. ses hazardous to health may be formed. breathing apparatus and full protective clothing must be worn in case of fire. Irs from fire area if you can do so without risk. irefighting procedures and consider the hazards of other involved materials. e or explosion hazards noted. Accidental release measures sary personnel away. Keep people away from and upwind of spill/leak. Wear
edical personnel are aware of the material(s) involved, and take precautions to elves. 5. Fire-fighting measures Im. Dry chemical powder. Carbon dioxide (CO2). ter jet as an extinguisher, as this will spread the fire. ses hazardous to health may be formed. breathing apparatus and full protective clothing must be worn in case of fire. Irs from fire area if you can do so without risk. irefighting procedures and consider the hazards of other involved materials. e or explosion hazards noted. Accidental release measures sary personnel away. Keep people away from and upwind of spill/leak. Wear
5. Fire-fighting measures am. Dry chemical powder. Carbon dioxide (CO2). ter jet as an extinguisher, as this will spread the fire. ses hazardous to health may be formed. breathing apparatus and full protective clothing must be worn in case of fire. rrs from fire area if you can do so without risk. irrefighting procedures and consider the hazards of other involved materials. e or explosion hazards noted. Accidental release measures sary personnel away. Keep people away from and upwind of spill/leak. Wear
 am. Dry chemical powder. Carbon dioxide (CO2). ter jet as an extinguisher, as this will spread the fire. ses hazardous to health may be formed. breathing apparatus and full protective clothing must be worn in case of fire. ars from fire area if you can do so without risk. arefighting procedures and consider the hazards of other involved materials. are or explosion hazards noted. Accidental release measures sary personnel away. Keep people away from and upwind of spill/leak. Wear
 am. Dry chemical powder. Carbon dioxide (CO2). ter jet as an extinguisher, as this will spread the fire. ses hazardous to health may be formed. breathing apparatus and full protective clothing must be worn in case of fire. ars from fire area if you can do so without risk. arefighting procedures and consider the hazards of other involved materials. are or explosion hazards noted. Accidental release measures sary personnel away. Keep people away from and upwind of spill/leak. Wear
ter jet as an extinguisher, as this will spread the fire. ses hazardous to health may be formed. breathing apparatus and full protective clothing must be worn in case of fire. rs from fire area if you can do so without risk. firefighting procedures and consider the hazards of other involved materials. e or explosion hazards noted. Accidental release measures sary personnel away. Keep people away from and upwind of spill/leak. Wear
breathing apparatus and full protective clothing must be worn in case of fire. In the second
rs from fire area if you can do so without risk. Firefighting procedures and consider the hazards of other involved materials. The or explosion hazards noted. Accidental release measures sary personnel away. Keep people away from and upwind of spill/leak. Wear
irefighting procedures and consider the hazards of other involved materials. e or explosion hazards noted. Accidental release measures sary personnel away. Keep people away from and upwind of spill/leak. Wear
e or explosion hazards noted. Accidental release measures sary personnel away. Keep people away from and upwind of spill/leak. Wear
Accidental release measures sary personnel away. Keep people away from and upwind of spill/leak. Wear
sary personnel away. Keep people away from and upwind of spill/leak. Wear
uld be advised if significant spillages cannot be contained. For personal protection, of the SDS.
miscible in water. Prevent product from entering drains.
top the flow of material, if this is without risk. Dike the spilled material, where this is r with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth containers. Following product recovery, flush area with water.
/ipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to al contamination.
pills to original containers for re-use. For waste disposal, see section 13 of the SDS.
to the environment. Inform appropriate managerial or supervisory personnel of all releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into ourses or onto the ground.
7. Handling and storage
ed exposure. Provide adequate ventilation. Wear appropriate personal protective oid release to the environment. Observe good industrial hygiene practices.
al tightly closed container. Store away from incompatible materials (see Section 10
sure controls/personal protection
· ·
nants (29 CFR 1910.1000) Type Value Form
PEL 5 mg/m3 Mist.
al S

Components	Туре	Value	Form
		2000 mg/m3 500 ppm	
US. ACGIH Threshold Lim			
Components	Туре	Value	Form
Distillates, (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide			
Components	Туре	Value	Form
Distillates, (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
,	STEL	10 mg/m3	Mist.
		•	
	TWA	5 mg/m3	Mist.
US. Workplace Environme	TWA	•	Mist.
US. Workplace Environme Components		•	Mist. Form
	TWA ental Exposure Level (WEEL) Guides	5 mg/m3	
Components Propylene glycol (CAS	TWA ental Exposure Level (WEEL) Guides Type	5 mg/m3 Value 10 mg/m3	Form
Components Propylene glycol (CAS 57-55-6)	TWA ental Exposure Level (WEEL) Guides Type TWA	5 mg/m3 Value 10 mg/m3 the ingredient(s). air changes per hour) should plicable, use process enclosu ain airborne levels below reco	Form Aerosol. be used. Ventilation rates ures, local exhaust ventilation ommended exposure limits. If
Components Propylene glycol (CAS 57-55-6) plogical limit values propriate engineering ntrols	TWA ental Exposure Level (WEEL) Guides Type TWA No biological exposure limits noted for Good general ventilation (typically 10 a should be matched to conditions. If ap or other engineering controls to mainta	5 mg/m3 Value 10 mg/m3 the ingredient(s). air changes per hour) should plicable, use process enclosu ain airborne levels below reco hed, maintain airborne levels	Form Aerosol. be used. Ventilation rates ures, local exhaust ventilation ommended exposure limits. If
Components Propylene glycol (CAS 57-55-6) blogical limit values propriate engineering ntrols	TWA ental Exposure Level (WEEL) Guides Type TWA No biological exposure limits noted for Good general ventilation (typically 10 a should be matched to conditions. If ap or other engineering controls to mainta exposure limits have not been establis	5 mg/m3 Value 10 mg/m3 the ingredient(s). air changes per hour) should plicable, use process enclosu ain airborne levels below reco hed, maintain airborne levels nt	Form Aerosol. be used. Ventilation rates ures, local exhaust ventilation ommended exposure limits. If
Components Propylene glycol (CAS 57-55-6) ological limit values propriate engineering htrols	TWA ental Exposure Level (WEEL) Guides Type TWA No biological exposure limits noted for Good general ventilation (typically 10 a should be matched to conditions. If ap or other engineering controls to mainta exposure limits have not been establis es, such as personal protective equipme	5 mg/m3 Value 10 mg/m3 the ingredient(s). air changes per hour) should plicable, use process enclosu ain airborne levels below reco hed, maintain airborne levels nt	Form Aerosol. be used. Ventilation rates ures, local exhaust ventilation ommended exposure limits. If
Components Propylene glycol (CAS 57-55-6) ological limit values propriate engineering htrols ividual protection measures Eye/face protection	TWA ental Exposure Level (WEEL) Guides Type TWA No biological exposure limits noted for Good general ventilation (typically 10 a should be matched to conditions. If ap or other engineering controls to mainta exposure limits have not been establis es, such as personal protective equipme	5 mg/m3 Value 10 mg/m3 the ingredient(s). air changes per hour) should plicable, use process enclosu ain airborne levels below reco hed, maintain airborne levels nt	Form Aerosol. be used. Ventilation rates ures, local exhaust ventilation ommended exposure limits. If
Components Propylene glycol (CAS 57-55-6) ological limit values propriate engineering htrols ividual protection measures Eye/face protection Skin protection	TWA ental Exposure Level (WEEL) Guides Type TWA No biological exposure limits noted for Good general ventilation (typically 10 a should be matched to conditions. If ap or other engineering controls to mainta exposure limits have not been establis es, such as personal protective equipme Wear safety glasses with side shields of	5 mg/m3 Value 10 mg/m3 the ingredient(s). air changes per hour) should plicable, use process enclosu ain airborne levels below reco hed, maintain airborne levels nt	Form Aerosol. be used. Ventilation rates ures, local exhaust ventilation ommended exposure limits. If
Components Propylene glycol (CAS 57-55-6) ological limit values propriate engineering htrols ividual protection measures Eye/face protection Skin protection Hand protection	TWA ental Exposure Level (WEEL) Guides Type TWA No biological exposure limits noted for Good general ventilation (typically 10 a should be matched to conditions. If app or other engineering controls to mainta exposure limits have not been establis es, such as personal protective equipme Wear safety glasses with side shields of Wear protective gloves.	5 mg/m3 Value 10 mg/m3 the ingredient(s). air changes per hour) should plicable, use process enclosu ain airborne levels below reco hed, maintain airborne levels nt (or goggles).	Form Aerosol. be used. Ventilation rates ures, local exhaust ventilatior ommended exposure limits. If

9. Physical and chemical prop

Appearance	
Physical state	Liquid.
Form	Clear Liquid.
Color	Amber
Odor	Mild
Odor threshold	Not available.
рН	9.0 - 10.0
Melting point/freezing point	< 40 °F (< 4.4 °C) estimated
Initial boiling point and boiling	> 212 °F (> 100 °C) estimated
range	
Flash point	None
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)Not available.Explosive limit - upper (%)Not available.Vapor pressure< 1.0 mm Hg estimated	
Vapor pressure< 1.0 mm Hg estimated	
Vapor densityNot available.Relative densityNot available.Solubility(ies)CompleteSolubility (water)CompletePartition coefficient (n-octanol/water)Not available.Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.Other informationI.00 g/cm3 8.35 lb/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.Percent volatile> 40 % estimated 9.3 (5% Emulsion)	
Relative densityNot available.Solubility(ies)CompleteSolubility (water)CompletePartition coefficient (n-octanol/water)Not available.Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.Other informationI.00 g/cm3 8.35 lb/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.Percent volatile> 40 % estimated 9.3 (5% Emulsion)	
Solubility(ies) Solubility (water)CompletePartition coefficient (n-octanol/water)Not available.Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.Other information Density1.00 g/cm3 8.35 lb/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.Percent volatile pH in aqueous solution> 40 % estimated 9.3 (5% Emulsion)	
Solubility (water)CompletePartition coefficient (n-octanol/water)Not available.Auto-ignition temperatureNot available.Decomposition temperatureNot available.UiscosityNot available.Other information1.00 g/cm3 8.35 lb/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.Percent volatile> 40 % estimated 9.3 (5% Emulsion)	
Partition coefficient (n-octanol/water)Not available.Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.Other informationI.00 g/cm3 8.35 lb/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.Percent volatile> 40 % estimated 9.3 (5% Emulsion)	
(n-octanol/water)Not available.Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.Other information1.00 g/cm3 8.35 lb/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.Percent volatile> 40 % estimated 9.3 (5% Emulsion)	
Decomposition temperatureNot available.ViscosityNot available.Other information1.00 g/cm3 8.35 lb/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.Percent volatile> 40 % estimated 9.3 (5% Emulsion)	
ViscosityNot available.Other information1.00 g/cm3 8.35 lb/galDensity1.00 g/cm3 8.35 lb/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.Percent volatile> 40 % estimatedpH in aqueous solution9.3 (5% Emulsion)	
Other informationDensity1.00 g/cm3 8.35 lb/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.Percent volatile> 40 % estimatedpH in aqueous solution9.3 (5% Emulsion)	
Density1.00 g/cm3 8.35 lb/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.Percent volatile> 40 % estimatedpH in aqueous solution9.3 (5% Emulsion)	
8.35 lb/galExplosive propertiesOxidizing propertiesNot oxidizing.Percent volatilepH in aqueous solution9.3 (5% Emulsion)	
Oxidizing propertiesNot oxidizing.Percent volatile> 40 % estimatedpH in aqueous solution9.3 (5% Emulsion)	
Percent volatile> 40 % estimatedpH in aqueous solution9.3 (5% Emulsion)	
pH in aqueous solution 9.3 (5% Emulsion)	
Specific gravity 1.00	
VOC (Weight %) 2.4 % w/w ASTM E1868	8-10

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.	
Skin contact	No adverse effects due to skin contact are expected.	
Eye contact	Direct contact with eyes may cause temporary irritation.	
Ingestion	Expected to be a low ingestion hazard.	
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.	
Information on toxicological effe	ects	
Acute toxicity	Not available.	
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory or skin sensitization	1	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
Material name: XTREME CUIT 220C		600

IARC Monographs, Overall	Evaluation of Carcinogenicity
o-Phenylphenol (CAS 90	
Not listed.	
	ogram (NTP) Report on Carcinogens
Not available.	This product is not expected to cause reproductive or developmental effects.
Reproductive toxicity	Not classified.
Specific target organ toxicity - single exposure	NUT Classified.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	No known significant effects or critical hazards.
	12. Ecological information
Ecotoxicity	Toxic to aquatic life. Harmful to aquatic life with long lasting effects.
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	
Partition coefficient n-octan	
o-Phenylphenol Propylene glycol	3.09 -0.92
Mobility in soil	-0.92 No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation
Other adverse effects	potential, endocrine disruption, global warming potential) are expected from this component.
	13. Disposal considerations
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
	14. Transport information
DOT	-
Not regulated as dangerous g	joods.
ΙΑΤΑ	
Not regulated as dangerous g	joods.
IMDG	
Not regulated as dangerous g	
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not established.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not regulated as dangerous goods.
	15. Regulatory information
US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication
	Standard, 29 CFR 1910.1200.

Material name: XTREME CUT 220C 1992 Version #: 01 Issue date: 02-09-2016

.4)		
Listed.		
R 1910.1001-1050)		
1986 (SARA)		
No 0		
lo No		
CAS number	% by wt.	
55406-53-6 90-43-7	0.1 - 1 0.1 - 1	
Pollutants (HAPs) List		
elease Prevention (40 CFR	68.130)	
tment of Justice (California	a Health and Safety Code Section 11100)	
		,
Consumer Products Regula	ations (Cal. Code Regs, tit. 22, 69502.3, s	subd.
o-Know Act		
53-6)		
-to-Know Law		
53-6)		
nown to the State of Californ	ia to cause cancer and birth defects or othe	۶r
date/Carcinogenic substar	nce	
Listed: August 4,		
3 1 1		
	On inventory (w	es/no
es List (DSL)		Ye
	nina (IFCSC)	Ye
	s List (DSL) Chemical Substances in Cl	On inventory (y s List (DSL) Chemical Substances in China (IECSC)

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision		
Issue date	02-09-2016	
Version #	01	
Disclaimer	QualiChem, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.	