



MATERIAL SAFETY DATA SHEET

Product Name: Water Works™ Xtreme
Product Code: KET-WWXT

Effective Date: 4/08/2010
Page 1 of 7

The Keteca USA, Inc encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. Product and Company Identification

Product Name WATER WORKS™ Xtreme

COMPANY IDENTIFICATION

The Keteca USA, Inc
1725 W. Williams Drive
Bldg. F, Suite 68
Phoenix, AZ 85027
USA

Customer Information Number: 877-418-1306

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 602-278-7789
Local Emergency Contact: 602-278-7789

2. Hazards Identification

Emergency Overview

Color: Colorless

Physical State: Liquid

Odor: Ether

Hazards of product:

May cause eye irritation. May cause skin irritation. May cause a slipping hazard when spilled.

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. May cause a slipping hazard when spilled.

Potential Health Effects

Eye Contact: May cause slight eye irritation. May cause slight corneal injury.

Skin Contact: Prolonged contact may cause slight skin irritation with local redness.

Skin Absorption: Prolonged skin contact is unlikely to result in absorption of harmful amounts.

Inhalation: Prolonged exposure is not expected to cause adverse effects.

Ingestion: Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

Effects of Repeated Exposure: None known.

MATERIAL SAFETY DATA SHEET

Product Name: Water Works™ Xtreme
Product Code: KET-WWXT

Effective Date: 4/08/2010
Page 2 of 7

3. Composition Information

Composition (648/2004/EC): Less than <=20.0% non-ionic surfactants, anionic surfactants.

Hazardous Components:

<u>Component</u>	<u>CAS #</u>	<u>Amount</u>	<u>Labeling</u>
N,N Diethanolamine	111-42-2		Xn: R22, R48/22 Xi: R38, R41
D-Limonene (Food Grade)	5989-27-5		Xi: R10, R38/ R43 R50/53

4. First-aid Measures

Eye Contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Skin Contact: Wash skin with plenty of water.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Ingestion: If swallowed, seek medical attention. Do not induce vomiting unless directed to do so by medical personnel.

Notes to Physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. Fire Fighting Measures

Extinguishing Media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Fire Fighting Procedures: Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Avoid accumulation of water.

Special Protective Equipment for Firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

Hazardous Combustion Products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide. Aldehydes. Ketones. Organic acids.

MATERIAL SAFETY DATA SHEET

Product Name: Water Works™ Xtreme
Product Code: KET-WWXT

Effective Date: 4/08/2010
Page 3 of 7

6. Accidental Release Measures

Steps to be Taken if Material is Released or Spilled: Small spills: Absorb with materials such as: Sand. Vermiculite. Collect in suitable and properly labeled containers. Large spills: Contain spilled material if possible. Pump into suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

Personal Precautions: Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental Precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

7. Handling and Storage

Handling

General Handling: Avoid contact with eyes. Wash thoroughly after handling. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Other Precautions: Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

Storage: No specific requirements. Store below 90°F away from direct sunlight.

Shelf life: 24 Months

8. Exposure Controls / Personal Protection

Exposure Limits None known.

Personal Protection

Eye/Face Protection: Use chemical goggles.

Skin Protection: Wear clean, body-covering clothing.

Hand protection: Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Examples of preferred glove barrier materials include: Butyl rubber. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors.

Respiratory Protection: Wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge.

Ingestion: Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating.

Engineering Controls

Ventilation: General ventilation should be sufficient for most operations

Product Name: Water Works™ Xtreme
Product Code: KET-WWXTEffective Date: 4/08/2010
Page 4 of 7

9. Physical and Chemical Properties

Physical State	Liquid
Color	Colorless
Odor	Light Citrus
Flash Point - Closed Cup	148 Test Method SW1010 A
Flammable Limits In Air Lower:	0.6 %(V) <i>Literature</i>
Upper	20.4 %(V) <i>Literature</i>
Autoignition Temperature	194 °C (381 °F) <i>Literature</i>
Vapor Pressure	< 0.04 mmHg @ 20 °C <i>Literature</i>
Boiling Point (760 mmHg)	230 °C (446 °F) <i>Literature</i> .
Vapor Density (air = 1)	6.60 <i>Literature</i>
Specific Gravity (H2O = 1)	0.910 25 °C/25 °C <i>Literature</i>
Freezing Point	No test data available
Melting Point	No test data available
Solubility in Water (by weight)	4.5 % @ 25 °C <i>Literature</i>
pH	9.0 – 10.0
Octanol/Water Partition Coefficient	1.13 <i>Estimated</i>
Dynamic Viscosity	4.9 mPa.s @ 25 °C <i>Literature</i>
VOC Content	<2 g/L when used as directed.

10. Stability and Reactivity

Stability/Instability

Stable under recommended storage conditions. See Storage, Section 7.

Conditions to Avoid: Product can oxidize at elevated temperatures.

Generation of gas during decomposition can cause pressure in closed systems.

Incompatible Materials: Avoid contact with: Strong acids. Strong bases. Strong oxidizers.

Hazardous Polymerization

Will not occur.

Thermal Decomposition

Decomposition products depend upon temperature, air supply and the presence of other materials.

Decomposition products can include and are not limited to: Aldehydes. Ketones. Organic acids.

11. Toxicological Information

Acute Toxicity

Ingestion

No data available.

Skin Absorption

No data available.

Inhalation

No data available.

Sensitization

Skin

No data available.



MATERIAL SAFETY DATA SHEET

Product Name: Water Works™ Xtreme
Product Code: KET-WWXT

Effective Date: 4/08/2010
Page 5 of 7

Repeated Dose Toxicity

No data available.

Developmental Toxicity

No data available.

Reproductive Toxicity

No data available.

Genetic Toxicology

12. Ecological Information

CHEMICAL FATE

Persistence and Degradability

Biodegradation Tests:

Fully biodegradable in accordance with ISO 9439.

ECOTOXICITY

No data available.

13. Disposal Considerations

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. KETECA USA, INC. HAS NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. As a service to its customers, Keteca USA can provide names of information resources to help identify waste management companies and other facilities which recycle, reprocess or manage chemicals or plastics, and that manage used drums. Telephone Keteca's Customer Information Group at 1-877-418-1306 or 602-278-7789.

14. Transport Information

DOT Non-Bulk

NOT REGULATED

DOT Bulk

NOT REGULATED

IMDG

NOT REGULATED

ICAO/IATA

NOT REGULATED

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the

MATERIAL SAFETY DATA SHEET

Product Name: Water Works™ Xtreme
Product Code: KET-WWXT

Effective Date: 4/08/2010
Page 6 of 7

transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. Regulatory Information

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. May cause a slipping hazard when spilled.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Immediate (Acute) Health Hazard	Yes
Delayed (Chronic) Health Hazard	No
Fire Hazard	No
Reactive Hazard	No
Sudden Release of Pressure Hazard	No

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Hazardous Substances List and/or Pennsylvania Environmental Hazardous Substance List:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

Pennsylvania (Worker and Community Right-To-Know Act): Pennsylvania Special Hazardous Substances List:

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this statute.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

US. Toxic Substances Control Act

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

CEPA - Domestic Substances List (DSL)

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

16. Other Information

Product Literature

Additional information on this product may be obtained by calling your sales or customer service contact.

Recommended Uses and Restrictions



MATERIAL SAFETY DATA SHEET

Product Name: Water Works™ Xtreme
Product Code: KET-WWXT

Effective Date: 4/08/2010
Page 7 of 7

Industrial solvent for cleaner and coating formulations. Use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact your sales or customer service representative.

Revision

Issue Date: 4/08/2010

Legend

N/A	Not available
W/W	Weight/Weight
OEL	Occupational Exposure Limit
STEL	Short Term Exposure Limit
TWA	Time Weighted Average
ACGIH	American Conference of Governmental Industrial Hygienists, Inc.
KETECA IHG	Keteca Industrial Hygiene Guideline
WEEL	Workplace Environmental Exposure Level
HAZ_DES	Hazard Designation
Action Level	A value set by OSHA that is lower than the PEL which will trigger the need for activities such as exposure monitoring and medical surveillance if exceeded.

Keteca USA, Inc urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that its activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.